

Alu tape included !

High density !

insulSound

Lowers the resonance of flexible parquet flooring

ΔL_w 17 dB



17 dB

High comfort rank !



AAA



Stops humidity



**inert
Clean**

Application

Under parquet flooring

Characteristics

Comfort classification : AAA
Acoustic insulation : ΔL_w 17dB
Value λ : 0,034 W/mK
Materials : closed-cell polyolefine foam
Thickness : \pm 2 mm
Standard size : 25 m x 1 m rolls
Colour : pearl beige
Aluminium tape provided : 25 m x 5 cm

Advantages

Lowers the resonance of parquet flooring
Reduces impact noise
Acoustic and thermal insulation
Easy and quick to lay
High density
Durable, will not tear on laying
Protects the parquet flooring from humidity
Aluminium tape provided
= completely impenetrable
Tested by CSTC : results guaranteed

insulSound

Double purpose :
Lowers the resonance of parquet flooring and insulates against impact noise

Description

InsulSound is a thin underlay for flexible and inflexible parquet flooring. InsulSound reduces impact noise and lowers the resonance from walking on laminated flooring. Moreover, InsulSound efficiently protects your parquet flooring from humidity.



Installation instructions

Laying the roll : The floor should be smooth and carefully brushed. Unroll InsulSound from one side of the room to the other leaving a surplus running slightly up each wall. Apply the supplied aluminium tape to the joints. Lay the parquet flooring and, only after this has been done, trim the surplus InsulSound. Attach the skirting board to the wall, slightly higher than the flexible flooring so that the two do not touch. Seal the gap between the skirting board and the flooring with a silicone sealant.



1. Unroll InsulSound wall to wall, leaving a surplus running up each wall



Advantage: the aluminium tape included with each roll of InsulSound makes the underlay completely impenetrable and thus protects the parquet flooring from humidity



2. Apply the aluminium tape to the joints



3. Place the parquet flooring, leaving the surplus underlay



4. Trim the surplus InsulSound



5. Attach the skirting board a few millimetres above the parquet flooring, then fill the gap with sealant

insulco
Technical products

Specialists in impact noise insulation

insulco sprl • Z.I. Sud (1) • Rue Buisson aux Loups 1a • 1400 Nivelles • BELGIUM

Tel : 0032 67 41 16 10 • Fax : 0032 67 41 16 16

e-mail : insulco@insulco.be • Web : www.insulit.com